


CRYOGEN FREE SUPERCONDUCTING MAGNET JMTD-2T300

Easy operation!
Compact and space saving!



Specifications for Superconducting Magnet

1. Scope of Supply

1-1 The followings are included:

- | | | |
|-----|-------------------------------------|--------|
| (1) | Superconducting Magnet | 1 unit |
| (2) | Compressor Unit (water cooled type) | 1 unit |
| (3) | Magnet Power Supply | 1 unit |
| (4) | Temperature Indicator | 1 unit |
| (5) | Flex Lines and Electrical Cables | 1 set |

1-2 The followings are not included

- | | |
|-----|---|
| (1) | Vacuum Pump |
| (2) | Spare Parts |
| (3) | Passive shield |
| (4) | Packing & Shipping (Optional) |
| (5) | Installation, setting, user training (Optional) |

2. Specifications

	Model	JMTD-2T300
(1)	Magnet	
	Type	solenoid
	Maximum central field	2 Tesla
	Maximum sweep rate	2 Tesla /10 minutes
	Field uniformity	less than 3%@ ϕ 200xh60mm (Design value)
	Initial cool down time from ambient	less than 72h
	Temperature monitoring points	1 (on coil)
	Axial 5 Gauss stray field limit from magnet center (w/o passive shield)	3.5 m (approximately)
	Radial 5 Gauss stray field limit from magnet center (w/o passive shield)	2.8 m (approximately)
	Persistent current switch	not applied
(2)	Cryostat	
	Type	cryogen free
	Room temperature bore diameter	300 mm
	Ambient Temperature direction	4-30 degree C

Specifications on this brochure may subject to change without notice

Japan Superconductor Technology, Inc.

Head Office

1-5-5 Takatsukadai Nishi-ku Kobe, Hyogo, 651-2271 Japan.
TEL: +81-78-277-0896 FAX: +81-78-336-9862

Tokyo Sales Office

Otemachi 2-1-1, Chiyoda-ku, Tokyo, 100-0004 Japan
TEL: +81-3-6756-9410 FAX: +81-3-6831-6150



URL: <https://www.jastec-inc.com>