

Easy operation!
Compact and space saving!



Specifications for Superconducting Magnet

1. Scope of Supply

1-1 The followings are included:

(1)	Superconducting Magnet	1 unit
(2)	Compressor Unit (water cooled type)	1 unit
(3)	Magnet Power Supply	2 unit
(4)	Temperature Indicator	2 unit
(5)	Flex Lines and Electrical Cables	1 set

1-2 The followings are not included

(1)	Vacuum Pump
(2)	Spare Parts
(3)	Passive shield
(4)	Packing & Shipping (Optional)
(5)	Installation, setting, user training (Optional)

2. Specifications

	Model	JMTD-5.8T280G
(1)	Magnet	
	Type	solenoid
	Maximum central field	5.8 Tesla
	Maximum sweep rate	Main Coil 5.8 Tesla / 70 minutes
	Axial Coil	10A / 10 minutes
	Initial cool down time from ambient	less than 300h
	Temperature monitoring points	2 (on coil and HTS Lead)
	Axial 5 Gauss stray field limit from magnet center (w/o passive shield)	5.7 m (approximately)
	Radial 5 Gauss stray field limit from magnet center (w/o passive shield)	4.6 m (approximately)
	Persistent current switch	not applied
(2)	Cryostat	
	Type	cryogen free
	Room temperature bore diameter	280 mm
	Ambient Temperature direction	4-30 degree C

Specifications on this brochure may subject to change without notice

Japan Superconductor Technology, Inc.

Head Office

1-5-5 Takatsukadai Nishi-ku Kobe, Hyogo, 651-2271 Japan.
TEL: +81-78-277-0896 FAX: +81-78-336-9862

Tokyo Sales Office

Otemachi 2-1-1, Chiyoda-ku, Tokyo, 100-0004 Japan
TEL: +81-3-6756-9410 FAX: +81-3-6831-6150



URL: <https://www.jastec-inc.com>